### **AlcoMate Prestige**

Model: AL6000



# Thanks to the field replaceable and pre-calibrated sensor module, you will never have to send in your breathalyzer for calibration

The AlcoMate Prestige breathalyzer comes with an innovative and patent pending technology that allows users to re-calibrate their breathalyzer without the need for shipping their device to ASD. Prestige users themselves can now swap the sensor module with a factory pre-calibrated one and save not only on cost but also more importantly they eliminate the risk of being without their breathalyzer while it is out for calibration.

Sensor swapping is an ideal solution for all users, especially for clinics, field officers, or for devices on board a vessel in the open sea. Now vessel operators and clinics can have their breathalyzer always accurate and always ready for immediate breath alcohol testing.

#### Features

- No Calibration Needed!
- DOT / FDA / Coast Guard Approved
- Easy to Replace Sensor Modules
- Bright LED Display
- Active Pressure Sensor
- Deep-Lung Air Sampling
- Cumulative Test Counter
- Audible Alerts / Low Battery Indicator
- Auto Power Off

# For Availability & Pricing Call 866-216-8700

#### Why do pre-calibrated sensors make the AL6000 better than the competition?

The pre calibrated, field replaceable sensor has eliminated delays and complications of recalibration by allowing users to simply "snap out" an old sensor and "snap in" a new one. Restoring a reliable and accurate testing takes only a matter of seconds.



#### Package Contents:

- AlcoMate Prestige Unit
- Hard Carrying Case (perfect for the field)
- Carrying Pouch
- 5 Mouthpieces
- Hand Strap
- 2 AA Batteries
- Retail Box
- User's Guide



Technical Specifications	
Sensor:	Oxide Semiconductor
Material:	Silver or Red w/black Trim
Power:	1.5v AA Batteries x2 (Included)
Breath Sampling Time:	~5 seconds
Recalibration Need:	None* (*replaceable sensors should be replaced every 300 tests or at least annually)
Mouthpieces:	Advanced Disposable Mouthpieces
Operational Range:	0.00 to 0.40%BAC
Display	3-Digit Decimal Ultra Bright LCD Display
Sensor Accuracy:	+/- 0.01 at 0.05%
Size:	137 mm x 73 mm x 44 mm
Weight:	1.8 ounces (w/o batteries)





Advanced Safety Devices, LLC :: 21430 Strathern St Unit M Canoga Park, CA 91304 :: www.safety-devices.com Telephone: 818-701-9200 :: Fax: 818-701-9220 :: sales@safety-devices.com